

REM-11 (E-4) HAULAGE



FEATURES & BENEFITS

- Unique non-directional tread design for added traction
- Special compounds to withstand severe rock mining applications and extend tire life/promote retreadability
- Compounds: **A** cut/chip; **S** standard; **B** heat

PRODUCT CODE	TIRE SIZE	PATTERN	LOAD SYMBOL	SPEED MAX (KM/H)	SPEED MAX (MPH)	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	TREAD DEPTH (32NDS)	RIM	SINGLE MAX/LOAD PRESSURE (LBS/PSI)	TIRE WEIGHT	NOTE
1087133313	33.00R51	REM-11A	★★	50	30	120	35	111	24.00/5.0	85429lbs/98psi	2408kg/5308lbs	E4
1087133311	33.00R51	REM-11S	★★	50	30	120	35	111	24.00/5.0	85429lbs/98psi	2408kg/5308lbs	E4
1087133312	33.00R51	REM-11B	★★	50	30	120	35	111	24.00/5.0	85429lbs/98psi	2408kg/5308lbs	E4
1087133778	37.00R57	REM-11A	★★	50	30	135	41	123	27.00/6.0	116845lbs/102psi	3212kg/7081lbs	E4
1087133776	37.00R57	REM-11S	★★	50	30	135	41	123	27.00/6.0	116845lbs/102psi	3212kg/7081lbs	E4
1087133777	37.00R57	REM-11B	★★	50	30	135	41	123	27.00/6.0	116845lbs/102psi	3212kg/7081lbs	E4
1087134078	40.00R57	REM-11A	★★	50	30	141	44	123	29.00/6.0	132277lbs/102psi	3628kg/7998lbs	E4
1087134076	40.00R57	REM-11S	★★	50	30	141	44	123	29.00/6.0	132277lbs/102psi	3628kg/7998lbs	E4
1087134077	40.00R57	REM-11B	★★	50	30	141	44	123	29.00/6.0	132277lbs/102psi	3628kg/7998lbs	E4