

REM-6 (IND) INDUSTRIAL LUG



FEATURES & BENEFITS

- Flat tread-face provides optimum performance and wear
- Offers optimum stability and reduced lateral movement
- Special tread compounds fight rapid wear

PRODUCT CODE	TIRE SIZE	PATTERN	LOAD SYMBOL	SPEED MAX (KM/H)	SPEED MAX (MPH)	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	TREAD DEPTH (32NDS)	RIM	SINGLE MAX/LOAD PRESSURE (LBS/PSI)	TIRE WEIGHT	NOTE
1106355086	5.00R8	REM-6	111A5	35	22	18	5	31	3.00D	2398lbs/145psi	10kg/23lbs	-
1106356096	6.00R9	REM-6	121A5	35	22	21	6	31	4.00E	3190lbs/145psi	17kg/37lbs	-
1106356505	6.50R10	REM-6	128A5	35	22	23	7	34	5.00	3968lbs/145psi	20kg/44lbs	-
1106357026	7.00R12	REM-6	136A5	35	22	26	7	35	5.00S	4928lbs/145psi	27kg/59lbs	-
1106353156	315/70R15	REM-6	165A5	35	22	33	12	45	8.00	11330lbs/145psi	59kg/130lbs	-
1106357056	7.00R15	REM-6	143A5	35	22	29	8	35	5.50	5995lbs/145psi	32kg/69lbs	-
1106357556	7.50R15	REM-6	146A5	35	22	30	8	38	6.00	6600lbs/145psi	27kg/59lbs	-
1106358255	8.25R15	REM-6	153A5	35	22	33	9	40	6.50	8050lbs/145psi	47kg/104lbs	-
1106352275	225/75R15	REM-6	149A5	35	22	28	9	31	7.00	7150lbs/145psi	32kg/70lbs	-
1106352575	250/70R15	REM-6	153A5	35	22	29	10	33	7.00	8030lbs/145psi	35kg/77lbs	-
1106351006	10.00R20	REM-6	166A5	35	22	42	12	44	7.50	11660lbs/145psi	87kg/191lbs	-
1106351206	12.00R20	REM-6	176A5	35	22	45	13	52	8.50	15620lbs/145psi	126kg/252lbs	-
1106351246	12.00R24	REM-6	178A5	35	22	49	13	49	8.50	16500lbs/145psi	131kg/288lbs	-
1106354241	14.00R24	REM-6	193A5	25	22	56	15	81	10.00	24530lbs/145psi	232kg/506lbs	-
1106351625	16.00R25	REM-6	200A5	25	15.5	59	17	71	11.25/2.0	30860lbs/145psi	267kg/589lbs	-
1106351825	18.00R25	REM-6	207A5	25	15.5	65	20	81	13.00/2.5	38500lbs/145psi	396kg/865lbs	-
1106351833	18.00R33	REM-6	219A5	25	15.5	72	19	93	13.00/2.5	53572lbs/145psi	504kg/1111lbs	-