

REM-10

(E-3+/L-3+)
HAULAGE/ARTICULATED



FEATURES & BENEFITS

- Multi-function, non-directional tread design for optimum usage on equipment
- Superior traction in sand, stone, mud and other surfaces
- Unique center block tread design provides additional traction, enhanced smooth ride and even wear
- OEM Certified

PRODUCT CODE	TIRE SIZE	PATTERN	LOAD SYMBOL	SPEED MAX (KM/H)	SPEED MAX (MPH)	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	TREAD DEPTH (32NDS)	RIM	SINGLE MAX/LOAD PRESSURE (LBS/PSI)	TIRE WEIGHT	NOTE
1087106252	26.5R25	REM-10	★★	50	30	69	27	51	22.00/3.0	25300lbs/76psi	463kg/1023lbs	E3/L3
"	"	"	"	10	5	69	27	51	22.00/3.0	40700lbs/94psi	463kg/1023lbs	E3/L3
1087102955	29.5R25	REM-10	★★	50	30	74	29	55	25.00/3.5	30800lbs/76psi	597kg/1285lbs	E3/L3
"	"	"	"	10	5	74	29	55	25.00/3.5	49280lbs/94psi	597kg/1285lbs	E3/L3