

RLB1/RLB11*

PREMIUM OPEN SHOULDER
DRIVE POSITION TIRE



FEATURES & BENEFITS

- Open shoulder design provides excellent traction in wet and dry conditions; deep $26/32$ " tread depth for long original mileage
- Full-depth siping provides excellent performance throughout the life of the tread
- Heavy-duty casing for stability and promotion of retreading
- Tubeless and tube-type sizes for special applications

PRODUCT CODE	TIRE SIZE	PLY RATING	LOAD INDEX	SPEED SYMBOL	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	TREAD DEPTH (32NDS)	RIM	SINGLE MAX/LOAD PRESSURE	DUAL MAX/LOAD PRESSURE	STATIC LOAD RADIUS	REVS PER MILE	WEIGHT
1133412795	225/70R19.5	12	125/123	J	32.6	8.8	19	6.75	3640lbs/95psi	3415lbs/95psi	15.8	635	68
1133414796	245/70R19.5	16	136/134	J	33.5	9.6	19	7.50	4940lbs/120psi	4675lbs/120psi	15.2	617	84
1133415726	255/70R22.5	16	140/137	K	36.7	9.9	22	7.50	5510lbs/120psi	5070lbs/120psi	17.4	560	91
1133419206	9.00R20*	16	144/142	L	40.6	10.1	26	7.00	6175lbs/130psi	5840lbs/130psi	19.1	505	119
1133411026	10.00R20*	16	146/143	L	41.5	10.7	22	7.50	6610lbs/120psi	6005lbs/120psi	19.4	497	134
1133411206	11.00R20*	16	150/147	L	43.1	11.2	29	8.00	7390lbs/120psi	6780lbs/120psi	20.2	476	149
1133971208	11.00R20*	18	152/149	J	43.0	11.3	23	8.00	7830lbs/130psi	7160lbs/130psi	20.2	476	149
1133410225	10R22.5	14	141/139	K	40.2	10.0	22	7.50	5675lbs/115psi	5355lbs/115psi	18.3	512	112
1133411255	11R22.5	14	144/142	M	41.7	10.9	26	8.25	6175lbs/105psi	5840lbs/105psi	19.8	493	124
1133411256	11R22.5	16	148/145	M	41.7	10.9	26	8.25	6940lbs/123psi	6390lbs/123psi	19.8	493	128
1133419255	295/75R22.5	14	144/141	L	40.9	11.7	26	9.00	6175lbs/110psi	5675lbs/110psi	19.4	498	129
1133411455	11R24.5	14	146/143	L	43.7	10.9	26	8.25	6610lbs/105psi	6005lbs/105psi	21.0	471	137
1133411456	11R24.5	16	149/146	L	43.7	10.9	26	8.25	7160lbs/120psi	6610lbs/120psi	21.0	471	140
1133418455	285/75R24.5	14	144/141	L	41.9	11.0	26	8.25	6175lbs/110psi	5675lbs/110psi	19.8	485	134
1133419258	295/80R22.5	18	152/149	M	41.5	11.7	26	9.00	7830lbs/130psi	7160lbs/130psi	19.8	493	130