

REM-12

(L-5)
MINING LOADER



FEATURES & BENEFITS

- Unique non-directional tread design for added traction
- Special compounds to withstand severe rock mining applications
- Special cut/chip resistance compounds extend tire life and promote retreadability

PRODUCT CODE	TIRE SIZE	PATTERN	LOAD SYMBOL	SPEED MAX (KM/H)	SPEED MAX (MPH)	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	TREAD DEPTH (32NDS)	RIM	SINGLE MAX/LOAD PRESSURE (LBS/PSI)	TIRE WEIGHT	NOTE
1107127251	17.5R25	REM-12	★	6	3.7	55	19	84	14.00/1.5	15620lbs/73psi	251kg/563lbs	L5
1107126252	26.5R25	REM-12	★	10	5	71	27	116	22.00/3.0	33000lbs/65psi	651kg/1452lbs	L5
1107122955	29.5R25	REM-12	★	10	5	75	31	126	25.00/3.5	39600lbs/65psi	838kg/1672lbs	L5
1107137251	17.5R25	REM-12	★★	6	3.7	55	19	84	14.00/1.5	15620lbs/73psi	251kg/563lbs	L5
1107136252	26.5R25	REM-12	★★	10	5	71	27	116	22.00/3.0	33000lbs/73psi	657kg/1452lbs	L5
1107132955	29.5R25	REM-12	★★	10	5	75	31	126	25.00/3.5	39600lbs/73psi	846kg/1672lbs	L5